

Straight GHT Valve



Material

- Powder-coated zinc shut-off valve

Specifications

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**

Part #

GHV

GHT Ball Valve



Material

- Forged brass

Specifications

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**

Part #

500GHV

GHT Twin Valve



Material

- Powder-coated zinc with twin shut-off valves

Specifications

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**

Part #

GHYV

Garden Hose Y Valve



Feature

- Double Y valve, swivel inlet - with Higbee cut threads (capped) to prevent cross threading

Specifications

- Maximum temperature: **140°F (60°C)** (hot water)
- Working pressure: **100 PSI**

Material

- Forged brass

Part #

500GHY

Garden Hose Y Coupler



Material

- Nickel plated brass

Specifications

- Maximum working pressure: **100 PSI**
- Maximum temperature: **140°F (60°C)**

Part #

500YC

GHT Y



Feature

- Includes one end cap

Material

- Powder-coated zinc with twin outlet

Specifications

- Maximum temperature: **160°F (71°C)** (hot water)
- Recommended usage: **100°F (38°C)**
- Working pressure: **60 PSI**

Part #

GHY

H