

## Single Gallonage Constant Flow Nozzles



**Features:**

- for use up to **100 PSI** (water only)
- live swivel inlet
- spinning teeth

Size	Thread	Constant GPM @ 100 PSI	Aluminum Part #	Price/E
1"	NST (NH)	40	<b>AK4802F</b> <sup>1</sup>	<b>\$2065.95</b>
1½"	NST (NH)	125	<b>AK4820F</b> <sup>1</sup>	<b>2100.00</b>
2½"	NST (NH)	200	<b>AK4825F</b>	<b>2430.90</b>

<sup>1</sup> supplied with pistol grip

## Adjustable Constant Gallonage Constant Flow Nozzles



**Features:**

- for use up to **100 PSI** (water or foam only)
- live swivel inlet
- multiple flow settings for a combination of flow and control, tight, straight stream and wide, dense fog pattern
- quality flow performance as low as 50 PSI

Size	Thread	Constant GPM @ 100 PSI	Aluminum Part #	Price/E
1"	NST (NH)	13-25-40-60	<b>AK1702F</b> <sup>1</sup>	<b>\$3315.40</b>
1½"	NST (NH)	30-60-95-125	<b>AK1720F</b> <sup>1</sup>	<b>2993.80</b>
2½"	NST (NH)	125-150-200-250	<b>AK1725F</b>	<b>3423.65</b>

<sup>1</sup> supplied with pistol grip

## Ball Shutoff Nozzles - Bolted Style



**Features:**

- rugged and lightweight
- cast aluminum body with pistol grip
- hardcoated female swivel inlet and male outlet
- maximum operating pressure: **200 PSI** (water only) at 70°F (21°C)

Size	Thread	Waterway	Cast Aluminum Part #	Price/E
1½"	NST (NH)	1⅜"	<b>ACPSO150F</b>	<b>\$355.00</b>
1½"	NPSH	1⅜"	<b>ACPSO150</b>	<b>355.00</b>

P



## Pistol Grip Adapters



**Features:**

- converts any standard fog nozzle to a well-balanced, easy to hold pistol grip fog nozzle making the job of holding high pressure lines easier
- full-time ball bearing swivel base
- corrosion resistant
- heat treated aluminum construction for minimum weight
- hardcoated per MIL-A-8625-F TYPE 111, (Polylube 1)

Size	Thread	6061 T-6 Aluminum Part #	Price/E
1"	NST	<b>PGA100NST</b>	<b>\$463.95</b>
1½"	NST	<b>PGA150NST</b>	<b>463.95</b>
1½"	NPSH	<b>PGA150NPSH</b>	<b>463.95</b>
2½"	NST	<b>PGA250NST</b>	<b>601.40</b>