


Wilkerson Heavy Duty Modular Coalescing Filters



- for removal of extremely fine oil mists, oil aerosols and microscopic particles
- A standard airline filter should be installed as a pre-filter when using a coalescing filter.
- 1.0 micron type B1 and 0.003 micron type D elements are optional
- differential pressure indicator changes from green to red with pressure loss

Features:


- 0.01 micron type C element
- 1 qt. bowl
- differential pressure indicator eliminates the guesswork of element placement
- maximum operating conditions:
150 PSIG (10.3 bar) and **32°F to 150°F** (0°C to 65.5°C)



Size	Flow (SCFM)	With Metal Bowl	
		Automatic Drain	Price/E
1¼"	741	Part # M32-0AAMB	\$1775.75

Features:

- 0.01 micron type C element
- 1 qt. bowl
- differential pressure indicator eliminates the guesswork of element placement
- maximum operating conditions:
150 PSIG (10.3 bar) and **32°F to 150°F** (0°C to 65.5°C)



Size	Flow (SCFM)	With Metal Bowl	
		Automatic Drain	Price/E
1½"	710	Part # M35-0BAMB	\$1891.60
2"	710	Part # M35-0CAMB	1891.60

See pages 233-236 for filter accessories.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 150 PSIG inlet pressure.