


# Straight Through Quick-Connect Fittings

## Features:

- no internal valves, which provide maximum flow with minimum pressure drop
- interchanges with Parker-Hannifin SST/BST, Foster FST and Hansen ST couplings, see Hydraulic Profile Chart on page 850
- Do not disconnect with pressure in line. 

## Female Plugs

Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	steel	STFP2	\$2.77	12
3/8"	3/8" - 18	4500	steel	STFP3	4.37	12
1/2"	1/2" - 14	3500	steel	STFP4	6.14	12
3/4"	3/4" - 14	3100	steel	STFP6	14.17	12
1"	1" - 11 1/2	2500	steel	STFP8	26.56	1
1 1/4"	1 1/4" - 11 1/2	2500	steel	STFP10	61.96	1
1 1/2"	1 1/2" - 11 1/2	2500	steel	STFP12	99.61	1
2"	2" - 11 1/2	2500	steel	STFP16	127.41	1
1/4"	1/4" - 18	3800	brass	STFP2B	5.20	12
3/8"	3/8" - 18	2700	brass	STFP3B	6.60	12
1/2"	1/2" - 14	2200	brass	STFP4B	9.85	12
3/4"	3/4" - 14	1700	brass	STFP6B	15.60	12
1"	1" - 11 1/2	1200	brass	STFP8B	29.25	1
1 1/4"	1 1/4" - 11 1/2	1800	brass	E10F10-B	54.02	10
1 1/2"	1 1/2" - 11 1/2	1800	brass	E12F12-B	87.79	5
2"	2" - 11 1/2	1800	brass	E16F16-B	119.30	1
1/4"	1/4" - 18	6700	303 stainless	STFP2SS	17.80	5
3/8"	3/8" - 18	5500	303 stainless	STFP3SS	20.75	5
1/2"	1/2" - 14	3000	303 stainless	STFP4SS	47.00	5
3/4"	3/4" - 14	3000	303 stainless	STFP6SS	71.10	5
1"	1" - 11 1/2	1700	303 stainless	STFP8SS	128.50	5
1 1/4"	1 1/4" - 11 1/2	2000	303 stainless	E10F10-S	139.00	10
1 1/2"	1 1/2" - 11 1/2	2000	303 stainless	E12F12-S	243.24	5
2"	2" - 11 1/2	2000	303 stainless	E16F16-S	312.74	1



H

## Male Plugs

Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	steel	STMP2	\$2.77	12
3/8"	3/8" - 18	4500	steel	STMP3	4.37	12
1/2"	1/2" - 14	3500	steel	STMP4	6.14	12
3/4"	3/4" - 14	3100	steel	STMP6	14.17	12
1"	1" - 11 1/2	2500	steel	STMP8	26.56	1
1 1/4"	1 1/4" - 11 1/2	2500	steel	STMP10	69.49	1
1 1/2"	1 1/2" - 11 1/2	2500	steel	STMP12	99.61	1
2"	2" - 11 1/2	2500	steel	STMP16	133.20	1
1/4"	1/4" - 18	3800	brass	STMP2B	4.85	12
3/8"	3/8" - 18	2700	brass	STMP3B	6.00	12
1/2"	1/2" - 14	2200	brass	STMP4B	9.30	12
3/4"	3/4" - 14	1700	brass	STMP6B	13.70	12
1"	1" - 11 1/2	1600	brass	STMP8B	27.00	1
1 1/4"	1 1/4" - 11 1/2	1800	brass	E10M10-B	61.90	10
1 1/2"	1 1/2" - 11 1/2	1800	brass	E12M12-B	87.79	5
2"	2" - 11 1/2	1800	brass	E16M16-B	120.43	1
1/4"	1/4" - 18	6700	303 stainless	STMP2SS	15.90	5
3/8"	3/8" - 18	5500	303 stainless	STMP3SS	18.00	5
1/2"	1/2" - 14	3000	303 stainless	STMP4SS	43.00	5
3/4"	3/4" - 14	3000	303 stainless	STMP6SS	67.00	5
1"	1" - 11 1/2	1700	303 stainless	STMP8SS	136.50	5



## Standard Hose Barb Plugs <sup>1</sup>

Body Size	Hose ID	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4"	3800	brass	E2S2-B	\$5.16	100
3/8"	3/8"	2800	brass	E3S3-B	6.31	50
1/2"	1/2"	2200	brass	E4S4-B	12.05	25
3/4"	3/4"	1700	brass	E6S6-B	15.78	20
1"	1"	1700	brass	E8S8-B	34.42	10
1/4"	1/4"	5200	steel	E2S2	6.03	100
3/8"	3/8"	2800	steel	E3S3	7.80	50
1/2"	1/2"	2200	steel	E4S4	14.65	25
3/4"	3/4"	1700	steel	E6S6	18.53	20
1"	1"	1700	steel	E8S8	37.07	10



<sup>1</sup> Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon™ cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.