

Straight Through Quick-Connect Fittings

Features:

- couplers have no internal valves which provide maximum flow with minimum pressure drop
- Buna-N gasket seal
- interchanges with Parker-Hannifin SST/BST, Foster FST and Hansen ST couplings
- *Do not disconnect with pressure in line.*



Female Couplers


Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	brass	STFC2	\$8.37	12
3/8"	3/8" - 18	4500	brass	STFC3	10.33	12
1/2"	1/2" - 14	3500	brass	STFC4	14.91	12
3/4"	3/4" - 14	3100	brass	STFC6	28.69	12
1"	1" - 11 1/2	2500	brass	STFC8	41.30	1
1 1/4"	1 1/4" - 11 1/2	2500	brass	STFC10	111.56	1
1 1/2"	1 1/2" - 11 1/2	2500	brass	STFC12	152.90	1
2"	2" - 11 1/2	2500	brass	STFC16	210.64	1
1/4"	1/4" - 18	6700	303 stainless	STFC2SS	55.25	5
3/8"	3/8" - 18	5500	303 stainless	STFC3SS	80.50	5
1/2"	1/2" - 14	3000	303 stainless	STFC4SS	94.00	5
3/4"	3/4" - 14	3000	303 stainless	STFC6SS	161.25	5
1"	1" - 11 1/2	1700	303 stainless	STFC8SS	218.00	5
1 1/4"	1 1/4" - 11 1/2	2000	303 stainless	10EF10-S	294.22	10
1 1/2"	1 1/2" - 11 1/2	2000	303 stainless	12EF12-S	426.11	5
2"	2" - 11 1/2	2000	303 stainless	16EF16-S	507.29	1



H

Male Couplers

Body Size	NPTF Thread	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4" - 18	5500	brass	STMC2	\$8.37	12
3/8"	3/8" - 18	4500	brass	STMC3	10.33	12
1/2"	1/2" - 14	3500	brass	STMC4	14.91	12
3/4"	3/4" - 14	3100	brass	STMC6	28.69	12
1"	1" - 11 1/2	2500	brass	STMC8	41.30	1
1 1/4"	1 1/4" - 11 1/2	2500	brass	STMC10	111.56	10
1 1/2"	1 1/2" - 11 1/2	2500	brass	STMC12	152.90	5
2"	2" - 11 1/2	2500	brass	STMC16	210.64	1
1/4"	1/4" - 18	6700	303 stainless	STMC2SS	57.10	5
3/8"	3/8" - 18	5500	303 stainless	STMC3SS	72.00	5
1/2"	1/2" - 14	3000	303 stainless	STMC4SS	99.00	5
3/4"	3/4" - 14	3000	303 stainless	STMC6SS	172.50	5
1"	1" - 11 1/2	1700	303 stainless	STMC8SS	291.25	5



Standard Hose Barb Couplers ¹

Body Size	Hose ID	PSI at 70°F	Material	Part #	Price/E	Opt Qty
1/4"	1/4"	5200	brass	2ES2-B	\$12.45	100
3/8"	3/8"	2800	brass	3ES3-B	13.77	50
1/2"	1/2"	2200	brass	4ES4-B	22.37	25
3/4"	3/4"	1700	brass	6ES6-B	34.42	20
1"	1"	1700	brass	8ES8-B	47.04	10



¹ Operating pressures for the standard hose barbs utilizing hose barb end connections may be dramatically reduced to that of the hose rating and/or hose and end connection combination. Consult hose manufacturer's catalog for hose end connection ratings. If in doubt, test under controlled conditions for suitability to application. Dixon™ cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.