

CVV-Series Hydraulic Couplings


Features

- Contact Dixon® for pressure ratings and other technical information.
- Interchangeable with European Screw-Together, Inteva STG-Series, Faster CVV-Series, DNP PVV3, Voswinkel Type-HS

Specification

- Nitrile rubber seal standard, providing a temperature range of -13°F to 257°F (-25°C to 125°C)

European Female Threaded Couplers



| Body Size | Threads | Steel Part # |
|-----------|----------------------|--------------|
| 1/4" | 1/4" - 18 NPTF | 2CVVF2 |
| | 1/4" - 19 BSPP | 2CVVBF2 |
| | M14X1.5 | 2CVVFM1415 |
| 3/8" | 3/8" - 18 NPTF | 3CVVF3 |
| | 3/8" - 19 BSPP | 3CVVBF3 |
| | M16X1.5 | 3CVVFM1615 |
| 1/2" | 1/2" - 14 NPTF | 4CVVF4 |
| | 3/4" - 16 ORB | 4CVVOF4 |
| | 1/2" - 14 BSPP | 4CVVBF4 |
| | M18X1.5 | 4CVVFM1815 |
| | 7/8" - 14 ORB | 4CVVOF5 |
| 3/4" | M22X1.5 | 4CVVFM2215 |
| | 3/4" - 14 NPTF | 6CVVF6 |
| | 3/4" - 14 BSPP | 6CVVBF6 |
| 1" | M22X1.5 | 6CVVFM2215 |
| | 1" - 11-1/2 NPTF | 8CVVF8 |
| | 1" - 11 BSPP | 8CVVBF8 |
| 1-1/4" | 1-1/4" - 11-1/2 NPTF | 10CVVF10 |
| | 1-1/4" - 11 BSPP | 10CVVBF10 |

European Female Threaded Plugs



| Body Size | Threads | Steel Part # |
|-----------|----------------------|--------------|
| 1/4" | 1/4" - 18 NPTF | CVV2F2 |
| | 1/4" - 19 BSPP | CVV2BF2 |
| | M14X1.5 | CVV2FM1415 |
| 3/8" | 3/8" - 18 NPTF | CVV3F3 |
| | 3/8" - 19 BSPP | CVV3BF3 |
| | M16X1.5 | CVV3FM1615 |
| 1/2" | 1/2" - 14 NPTF | CVV4F4 |
| | 3/4" - 16 ORB | CVV4OF4 |
| | 1/2" - 14 BSPP | CVV4BF4 |
| | M18X1.5 | CVV4FM1815 |
| | 7/8" - 14 ORB | CVV4OF5 |
| 3/4" | M22X1.5 | CVV4FM2215 |
| | 3/4" - 14 NPTF | CVV6F6 |
| | 3/4" - 14 BSPP | CVV6BF6 |
| 1" | M22X1.5 | CVV6FM2215 |
| | 1" - 11-1/2 NPTF | CVV8F8 |
| | 1" - 11 BSPP | CVV8BF8 |
| 1-1/4" | 1-1/4" - 11-1/2 NPTF | CVV10F10 |
| | 1-1/4" - 11 BSPP | CVV10BF10 |

K